

ECO PHOENIX FIREBRIGHT 5kW CE/SE/SIA APPROVED MULTIFUEL STOVE.

All local regulations, including those referring to national and European Standards including BS EN 15287, BS 6999, BS 8303 must be complied with when installing this appliance.

A carbon monoxide alarm must be fitted to BS EN 50292

ENERGY RATING - A

NOMINAL HEAT OUTPUT – 5kW

MAX LOG LENGTH - 270 mm

EFFICIENCY WOOD -79.9%

Emissions CO	@ 0.07 %	<i>– Eco pass level to be less than 0.12</i>	<i>– Produced under Industry Standard Test Conditions (@13% O2)</i>
Emissions OGC	@ 53 Nmg/m3	<i>– Eco pass level to be less than 120</i>	<i>– Produced under Industry Standard Test Conditions (@13% O2)</i>
Emissions NOx	@ 93 Nmg/m3	<i>– Eco pass level to be less than 200</i>	<i>– Produced under Industry Standard Test Conditions (@13% O2)</i>
Particulate Matter	@ 36 Nmg/m3	<i>– Eco pass level to be less than 40</i>	<i>– Produced under Industry Standard Test Conditions (@13% O2)</i>

EFFICIENCY ANCIT – 80.4%

Emissions CO	@ 0.06%	<i>– Eco pass level to be less than 0.12</i>	<i>– Produced under Industry Standard Test Conditions (@13% O2)</i>
Emissions OGC	@ 18 Nmg/m3	<i>– Eco pass level to be less than 120</i>	<i>– Produced under Industry Standard Test Conditions (@13% O2)</i>
Emissions NOx	@ 72 Nmg/m3	<i>– Eco pass level to be less than 200</i>	<i>– Produced under Industry Standard Test Conditions (@13% O2)</i>
Particulate Matter	@ 10 Nmg/m3	<i>– Eco pass level to be less than 40</i>	<i>– Produced under Industry Standard Test Conditions (@13% O2)</i>

OVERALL STOVE DIMENSIONS.

HEIGHT (body in room) - 620 mm

HEIGHT (rear box in wall) - 551 mm

WIDTH (body in room inc top) - 552 mm

WIDTH (rear box in wall) 400 mm

DEPTH (body in room inc door) 106 mm

DEPTH (rear box in wall) 310 mm

DISTANCE FROM COMBUSTIBLES

TOP - 350 mm

SIDE - 100 mm

FRONT - 300 mm

HEARTH -The Hearth must be 125 mm (5") and made of solid construction (concrete, stone, brick)

FLUE "5 / 127 mm CENTRE OF TOP FLUE TO REAR OF convector box - 95 mm (vert) or 45 deg.

FIREBOARDS

SET - BRDE108SET

REAR- BRDE108BK (286 X 174 mm)

SIDE - BRDE108LH (270 X 320 mm)

SIDE - BRDE108RH (270 X 320 mm)

TOP - BRDE108BAF (318 x 286 mm)

GLASS

GLS5000GL (350 X 315 X 4 mm) X 2

GRATE BARS - 7 X CST0305GT

GRATE LINK BAR – GRT0003LB108 – 8 holes – 270 mm long.

TURN BAR - 1 X GRT107TB – 210 mm long.

LOG GUARDS

LOG0104PR – 2 per stove, Straight log bar – Each. Specify stove size when ordering.

ROPE

DOOR ROPE - ROP5000DR (14mm x 1900 mm)

LADDER ROPE - ROP5000LR (1280 mm long)

TOOL

TLS4000POT

FUEL IS NOT TO BE STORED AROUND ANY STOVE WHILE THE STOVE IS IN USE!