

**FIREVIEW 5kW FLAT TOP SLENDER CE APPROVED CLASS 1: BS EN 13240:2001 + Amd 12:2004 MULTIFUEL STOVE.**

## Product Fiche

**Commission Delegated Regulation (EU) 2015/1187**

**Energy Labelling of Local Space Heaters**

<b>Supplier`s Name or Trademark:</b>	<b>Woodwarm</b>
<b>Suppliers Model Identifier:</b>	<b>Fireview 5kW</b>
<b>Energy Efficiency Class of Model:</b>	<b>A</b>
<b>Nominal Heat Output to Room (kW):</b>	<b>5</b>
<b>Nominal Heat Output to Water (kW):</b>	<b>n/a</b>
<b>Seasonal Space Efficiency (%):</b>	<b>69.7</b>
<b>Net Efficiency (%):</b>	<b>79.7</b>

**EFFIENCY WOOD**                      **79.7%**  
**EFFIENCY ANCIT**                    **69.8%**

### **OVERALL STOVE DIMENSIONS.**

HEIGHT - 610 mm  
WIDTH - 555 mm  
DEPTH –322 mm

### **DISTANCE FROM COMBUSTIBLES WITHOUT HEAT DEFLECTOR:-**

TOP - 450 mm  
REAR - 700 mm  
SIDE - 450 mm  
FRONT – 300 mm

HEARTH - If stove is sat on the hearth, the Hearth needs to be a min of 125 mm (5”) and made of solid construction (concrete, stone, brick)

If the stove is on minimum of 100mm legs, the hearth can be superimposed 12 mm deep and made of non-combustible material (glass, steel, concrete)

### **DISTANCE FROM COMBUSTIBLES WITH A HEATSHIELD (OUR OWN TESTING)**

REAR FLUE ADAPTER CANNOT BE USED WITH A HEATSHIELD

WITH ONE HEAT DEFLECTOR REAR CAN BE REDUCED TO – 350mm (HEAT0031SD1)

WITH TWO HEAT DEFLECTORS REAR CAN BE REDUCED TO – 175mm (HEAT0031SD2)

FLUE 6” / 152 mm

CENTRE OF TOP FLUE TO REAR OF STOVE – 131 mm

HEIGHT TO CENTRE OF REAR FLUE 462 mm

RFA - ADD 185 mm TO TOTAL DEPTH OF STOVE - CENTRE LINE OF RFA TO BACK PLATE OF STOVE 115 mm

MAX LOG LENGTH 368 mm

**FUEL IS NOT TO BE STORED UNDER OR AROUND ANY STOVE WHILE THE STOVE IS IN USE!**

### **REGULATIONS AND INSTALLATIONS TO COMPLY WITH.**

All local regulations, including those referring to national and European Standards (BS EN 15287-1:2007), Installation of chimneys and flues for domestic appliances burning solid fuel (including wood and peat) and BS 8303. Code of practice for installation of domestic heating and cooking appliances burning solid mineral fuel need to be complied with when installing this appliance.