

PHOENIX 5kW FIREGEM CE/SE APPROVED MULTIFUEL STOVE.

REGULATIONS AND INSTALLATIONS TO COMPLY WITH.

All local regulations, including those referring to national and European Standards (BS EN 15287-1:2007), Installation of chimneys and flues for domestic appliances burning solid fuel (including wood and peat) and BS 8303. Code of practice for installation of domestic heating and cooking appliances burning solid mineral fuel need to be complied with when installing this appliance.

MAX LOG LENGTH 440 mm

NOMINAL HEAT OUTPUT	5kW
EFFICIENCY WOOD	82.9%
EFFICIENCY ANCIT	75.4%

OVERALL STOVE DIMENSIONS.

HEIGHT - 635 mm
WIDTH - 552 mm
DEPTH - 302 mm

DISTANCE FROM COMBUSTIBLES WITHOUT HEAT DEFLECTOR:-

TOP - 400 mm
REAR - 800 mm
SIDE - 500 mm
FRONT - 300 mm

HEARTH - The stove is on minimum of 75mm integrated legs so the hearth can be superimposed 12 mm deep and made of non-combustible material (glass, steel, concrete)

DISTANCE FROM COMBUSTIBLES WITH A HEATSHIELD (OUR OWN TESTING)

REAR FLUE ADAPTER CANNOT BE USED WITH A HEATSHIELD

WITH ONE HEAT DEFLECTOR REAR CAN BE REDUCED TO - 400mm (HEAT00107SD1)

WITH TWO HEAT DEFLECTORS REAR CAN BE REDUCED TO - 200mm (HEAT00107SD2)

FLUE 5"/ 127 mm

CENTRE OF TOP FLUE TO REAR OF STOVE - 97.5 mm

HEIGHT TO CENTRE OF REAR FLUE 480 mm

RFA - ADD 165 mm TO TOTAL DEPTH OF STOVE - CENTRE LINE OF RFA FLUE TO BACK PLATE OF STOVE 82.5 mm

OPTIONAL TURN THE RFA AROUND- ADD 215 mm TO TOTAL DEPTH OF STOVE, CENTRE LINE OF RFA FLUE TO BACK PLATE OF STOVE 131 mm

FIREBOARDS

SET - BRD0106SET

REAR- BRD0106BK (451 X 200 mm)

SIDE- BRD0106SD (198 X 420 mm) X2

BAFFLE

BAF0106BF

GLASS

GLS5000GL (350 X 315 X 4 mm) X 2

GRATE BARS:-

4 x CST0305GT

TURN BAR:-

1 X GRT107TB

LOG GUARDS

1 X LOG0100PR SPECIFY STOVE SIZE

ROPE

DOOR ROPE - ROP5000DR (1900 mm)

LADDER ROPE - ROP5000LR (1280 mm long)